

## Section 1 - Product and Company Identification

|                     |                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------|
| Material Name       | - Silver Coat Protection                                                                    |
| Chemical Category   | - Mixture                                                                                   |
| Product Code        | - Silver Coat Protection                                                                    |
| Product Description | - Asphalt Based Aluminum Reflective Roof Coating.                                           |
| Product Use         | - Roof Coating.                                                                             |
| Synonyms            | - Non-Fibered Aluminum Roof Coating                                                         |
| Distributor         | - Bergstrom Industries<br>850 Greenlick Hollow Rd<br>Mt Pleasant, PA 15666<br>United States |
| Telephone           |                                                                                             |
| Technical           | - +1 (203) 858-0080                                                                         |
| Emergency           | - 800-424-9300 - CHEMTREC                                                                   |
| Emergency           | - 703-527-3887 - CHEMTREC (Outside US)                                                      |

## Section 2 - Hazards Identification

### GHS HAZARDS AND PRECAUTIONS

Signal Word: **WARNING!**

- **Flammable liquid and vapor** (Category 3)
- **Causes Skin Irritation** (Category 2)
- **Causes Serious Eye Irritation** (Category 2A)
- **Specific target organ toxicity** (single exposure) – (Category 3)
- **Suspected to cause cancer** (Category 2)
- **Harmful if swallowed** (Category 4)

|                         |                                                                                                                                                                                                                                                                                                                                                               |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Prevention</b>       | Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Wear protective gloves/eye protection/face protection. Use only outdoors or in a well-ventilated area.                                                                                                                                                      |
| <b>Response</b>         | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. IF exposed or if you feel unwell: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. |
| <b>Storage/Disposal</b> | Store in a closed container. Store in a well-ventilated place. Keep Cool. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.                                                                                                                                                                 |



|               |                                                                                       |
|---------------|---------------------------------------------------------------------------------------|
| Physical Form | - Liquid                                                                              |
| Color         | - Silver/aluminum                                                                     |
| Odor          | - Mild Hydrocarbon.                                                                   |
| Flash Point   | - 105°F                                                                               |
| OSHA(HCS2012) | - Flammable Liquids - Category 3, Skin Corrosion/Irritation - Category 2, Serious Eye |

**Route Of Entry** Damage, Eye Irritation - Category 2A, Carcinogenicity - Category 2, Specific target organ toxicity (single exposure) – (Category 3), Acute Toxicity (oral) – Category 4  
 - Inhalation, Skin, Eye, Ingestion/Oral

## Potential Health Effects

### Inhalation

- Acute (Immediate)** - May cause respiratory irritation. May cause drowsiness or dizziness
- Chronic (Delayed)** - Refer to other information found in Section 11-Toxicology.

### Skin

- Acute (Immediate)** - May cause irritation.
- Chronic (Delayed)** - Repeated and prolonged exposure may be harmful. Repeated and prolonged exposure to the skin may cause dermatitis.

### Eye

- Acute (Immediate)** - Causes serious eye irritation.
- Chronic (Delayed)** - Repeated and prolonged exposure may cause irritation.

### Ingestion

- Acute (Immediate)** - Harmful if swallowed.
- Chronic (Delayed)** - Repeated and prolonged exposure may be harmful.

#### Carcinogenic Effects

|         | CAS       | IARC                         | NTP                 |
|---------|-----------|------------------------------|---------------------|
| Asphalt | 8052-42-4 | Group 2B-Possible Carcinogen | Under Consideration |

## Section 3 - Composition/Information on Ingredients

#### Hazardous Components

| Chemical Name                               | CAS         | % (wt)     | UN;EINECS         | LD50/LC50                                                                           | Classifications According to Regulation/Directive          | Other |
|---------------------------------------------|-------------|------------|-------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------|-------|
| Mineral Spirits                             | 8052-41-3   | 35% TO 45% | 232-489-3         |                                                                                     | <b>UN GHS:</b>                                             | NDA   |
| Asphalt                                     | 8052-42-4   | 35% TO 45% | NA1999, 232-490-9 | Ingestion/Oral-Rat LD50 · >5000 mg/kg Inhalation-Rat LC50 · >94.4 mg/m <sup>3</sup> | <b>UN GHS:</b> Carc. 2; Eye Irrit. 2A; Skin Irrit. 2       | NDA   |
| Aluminum                                    | 7429-90-5   | 10% TO 20% | 231-072-3         |                                                                                     | Water React.<br><b>UN GHS:</b> Pyr. Sol. 1; Water-react. 2 | NDA   |
| 1,2,4-Trimethylbenzene                      | 95-63-6     | 1% TO 5%   | 202-436-9         | Ingestion/Oral-Rat LD50 · 5 g/kg                                                    |                                                            | NDA   |
| Benzene, 1,3,5-trimethyl                    | 108-67-8    | 1% TO 5%   | UN2325, 203-604-4 |                                                                                     |                                                            | NDA   |
| Solvent naphtha (petroleum), light aromatic | 64742-95-6  | 1% TO 5%   | 265-199-0         | Ingestion/Oral-Rat LD50 · 8400 mg/kg                                                | <b>UN GHS:</b> Asp. Tox. 1; Carc. 1B Carc.Cat.2; R45       | NDA   |
| Perlite                                     | 130885-09-5 | 1% TO 5%   |                   |                                                                                     | <b>UN GHS:</b> Eye Irrit. 2A; Skin Irrit. 2 (Dry)          |       |

**This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.**

See Section 11 for Toxicological Information.

## Section 4 - First Aid Measures

|                           |                                                                                                                                                                                                     |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhalation</b>         | - Move victim to fresh air. If signs/symptoms continue, get medical attention. If breathing is difficult, give oxygen. If not breathing, give artificial respiration.                               |
| <b>Skin</b>               | - Immediately flush skin with soap and plenty of water. Call a physician if symptoms occur. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse.                        |
| <b>Eye</b>                | - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.        |
| <b>Ingestion</b>          | - If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. |
| <b>Notes to Physician</b> | - Aspiration of liquid into the lungs during swallowing or vomiting can cause lung inflammation, serious lung damage and even death from chemical pneumonitis.                                      |

## Section 5 - Fire Fighting Measures

|                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Extinguishing Media</b>                | - LARGE FIRE: Water spray, fog or regular foam.<br>SMALL FIRES: Dry chemical, CO <sub>2</sub> , water spray or regular foam.                                                                                                                                                                                                                                                                                                                         |
| <b>Unsuitable Extinguishing Media</b>     | - Do not use direct water stream as it may splatter the burning product.                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Firefighting Procedures</b>            | - Fight advanced or massive fires from safe distance or protected location. Avoid water in a straight hose stream as the stream will cause splatter and spread fire. If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. |
| <b>Unusual Fire and Explosion Hazards</b> | - Combustible liquid. Containers may explode when heated. May release irritating or toxic gases, fumes, or vapors.                                                                                                                                                                                                                                                                                                                                   |
| <b>Hazardous Combustion Products</b>      | - Carbon monoxide, carbon dioxide, hydrocarbons.                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Protection of Firefighters</b>         | - Fire fighters should wear complete protective clothing including self-contained breathing apparatus.                                                                                                                                                                                                                                                                                                                                               |
| <b>Flash Point</b>                        | - 105 °F(40.56°C) CC (Closed Cup)                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Explosion Limits</b>                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Upper</b>                              | - 6 %                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Lower</b>                              | - 0.9 %                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## Section 6 - Accidental Release Measures

|                                  |                                                                                                                                                                                                                                                    |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Personal Precautions</b>      | - Do not touch damaged containers or spilled material unless wearing appropriate protective clothing Stay upwind Ventilate the area before entry                                                                                                   |
| <b>Emergency Procedures</b>      | - ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area) Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up |
| <b>Environmental Precautions</b> | - Prevent entry into waterways, sewers, basements or confined areas Do NOT wash away into sewer                                                                                                                                                    |
| <b>Containment/Clean-up</b>      | - Contain and recover liquid when possible. Contain and/or absorb spill with inert                                                                                                                                                                 |

- Measures** material (e.g. sand, vermiculite), then place in suitable container. Do not flush to sewer or allow to enter waterways. Do not use water to flush spill area. Use appropriate Personal Protective Equipment (PPE)
- Prohibited Materials** - Avoid contact with strong oxidizing agents and acids.

## Section 7 - Handling and Storage

- Handling** - KEEP OUT OF THE REACH OF CHILDREN! Keep away from heat and ignition sources. Keep away from fire - No Smoking. Do not use in areas without adequate ventilation.
- Storage** - Store in a well-ventilated place. Keep container tightly closed. No open flames, no sparks and no smoking.
- Special Packaging Materials** - No data available
- Incompatible Materials or Ignition Sources** - Avoid contact with strong oxidizing agents and acids.

## Section 8 - Exposure Controls/Personal Protection

### Personal Protective Equipment

#### Pictograms



- Respiratory** - In case of insufficient ventilation, wear suitable respiratory equipment. If listed exposure limits are expected to be exceeded, use approved respiratory protection suitable for the hazard.
- Eye/Face** - Wear ANSI approved safety glasses with side shields or safety goggles.
- Hands** - Wear chemical protective gloves made of Nitrile or Neoprene.
- Skin/Body** - Wear clothing that covers the skin to prevent skin exposure.
- General Industrial Hygiene Considerations** - Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling. Avoid breathing vapors.
- Engineering Measures/Controls** - Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.

### Exposure Limits/Guidelines

|                                     | Result | Canada Ontario                                                                        | Mexico                          | NIOSH                                                                            | OSHA                                                                                 | United States - California                                                           |
|-------------------------------------|--------|---------------------------------------------------------------------------------------|---------------------------------|----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| 1,2,4-Trimethylbenzene (95-63-6)    | TWAs   | Not established                                                                       | Not established                 | 25 ppm TWA; 125 mg/m <sup>3</sup> TWA                                            | Not established                                                                      | Not established                                                                      |
| Benzene, 1,3,5-trimethyl (108-67-8) | TWAs   | Not established                                                                       | Not established                 | 25 ppm TWA; 125 mg/m <sup>3</sup> TWA                                            | Not established                                                                      | Not established                                                                      |
| Aluminum (7429-90-5)                | TWAs   | 5 mg/m <sup>3</sup> TWAEV (powder); 10 mg/m <sup>3</sup> TWAEV (metal and oxide dust) | 10 mg/m <sup>3</sup> TWA (dust) | 10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable dust) | 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction) | 10 mg/m <sup>3</sup> PEL (total dust); 5 mg/m <sup>3</sup> PEL (respirable fraction) |
| Asphalt (8052-42-4)                 | TWAs   | 0.5 mg/m <sup>3</sup> TWAEV (fume, inhalable, as benzene-soluble aerosol)             | 5 mg/m <sup>3</sup> TWA         | Not established                                                                  | Not established                                                                      | 5 mg/m <sup>3</sup> PEL (fume)                                                       |
| Mineral Spirits                     | TWAs   | 525 mg/m <sup>3</sup> TWAEV                                                           | 100 ppm TWA; 523                | 350 mg/m <sup>3</sup> TWA                                                        | 500 ppm TWA; 2900                                                                    | 100 ppm PEL; 525                                                                     |

### Exposure Limits/Guidelines

|             | Result | Canada Ontario | Mexico    | NIOSH | OSHA      | United States - California |
|-------------|--------|----------------|-----------|-------|-----------|----------------------------|
| (8052-41-3) |        |                | mg/m3 TWA |       | mg/m3 TWA | mg/m3 PEL                  |

### Exposure Control Notations

ACGIH

- Asphalt (8052-42-4):Carcinogens:A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free)

### Key to abbreviations

PEL = Permissible Exposure Level determined by the Occupational Safety and Health Administration (OSHA)

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

## Section 9 - Physical and Chemical Properties

|                                           |                                                  |                                  |                                                     |
|-------------------------------------------|--------------------------------------------------|----------------------------------|-----------------------------------------------------|
| <b>Physical Form:</b>                     | Liquid                                           | <b>Appearance/Description:</b>   | Thick silver/aluminum semi-liquid.                  |
| <b>Color:</b>                             | Silver/aluminum                                  | <b>Odor:</b>                     | Mild Hydrocarbon.                                   |
| <b>Odor Threshold:</b>                    | No data available                                | <b>Boiling Point:</b>            | 300 to 390°F                                        |
| <b>Heat of Decomposition:</b>             | Not relevant                                     | <b>pH:</b>                       | Not relevant                                        |
| <b>Specific Gravity/Relative Density:</b> | = 0.98 Water=1                                   | <b>Density:</b>                  | = ~8.0 lbs/gal                                      |
| <b>Bulk Density:</b>                      | Not relevant                                     | <b>Water Solubility:</b>         | No                                                  |
| <b>Solvent Solubility:</b>                | Not relevant                                     | <b>Viscosity:</b>                | = 270 Centipoise (cPs, cP)<br>or mPas @ 140 F(60 C) |
| <b>Vapor Pressure:</b>                    | = 2 mmHg (torr) @ 68 F(20 C)                     | <b>Vapor Density:</b>            | = 4.9 Air=1                                         |
| <b>Evaporation Rate:</b>                  | < 1 Ether = 1                                    | <b>VOC (Wt.):</b>                | No data available                                   |
| <b>VOC (Vol.):</b>                        | < 400 g/L (West Coast)<br>< 450 g/L (East Coast) | <b>Volatiles (Wt.):</b>          | No data available                                   |
| <b>Volatiles (Vol.):</b>                  | No data available                                | <b>Flash Point:</b>              | 105 F(40.5556 C)                                    |
| <b>Flash Point Test Type:</b>             | CC (Closed Cup)                                  | <b>UEL:</b>                      | 6 %                                                 |
| <b>LEL:</b>                               | 0.9 %                                            | <b>Heat of Combustion (ΔHc):</b> | Not relevant                                        |

## Section 10 - Stability and Reactivity

|                                         |                                                         |
|-----------------------------------------|---------------------------------------------------------|
| <b>Stability</b>                        | - Stable under normal temperatures and pressures.       |
| <b>Hazardous Polymerization</b>         | - Hazardous polymerization not indicated.               |
| <b>Conditions to Avoid</b>              | - Avoid contact with strong oxidizing agents and flame. |
| <b>Incompatible Materials</b>           | - Strong oxidizers and acids.                           |
| <b>Hazardous Decomposition Products</b> | - Carbon monoxide, carbon dioxide and hydrocarbons.     |

## Section 11 - Toxicological Information

| Component Name         | Concentration | CAS       | Data                                                                                                                       |
|------------------------|---------------|-----------|----------------------------------------------------------------------------------------------------------------------------|
| Asphalt                | 35% TO 45%    | 8052-42-4 | Acute Toxicity: ; orl-rat LD50:>5000 mg/kg; ihl-rat LC50:>94.4 mg/m3<br>Tumorigen/Carcinogen: ; skn-mus TD :69 gm/kg/43W-I |
| 1,2,4-Trimethylbenzene | 1% TO 5%      | 95-63-6   | Acute Toxicity: ; orl-rat LD50:5 gm/kg; ihl-rat LC50:18000 mg/m3/4H                                                        |

| Component Name                              | Concentration | CAS        | Data                                                                                                  |
|---------------------------------------------|---------------|------------|-------------------------------------------------------------------------------------------------------|
| Benzene, 1,3,5-trimethyl                    | 1% TO 5%      | 108-67-8   | Acute Toxicity: ; orl-rat LD50:5000 mg/kg; ihl-hmn TClO:10 ppm<br>Irritation: ; skn-rbt 20 mg/24H MOD |
| Solvent naphtha (petroleum), light aromatic | 1% TO 5%      | 64742-95-6 | Acute Toxicity: ; orl-rat LD50:8400 mg/kg                                                             |

**Other Information**

- This product contains petroleum asphalt. Petroleum asphalt is not listed as a carcinogen by OSHA or NTP. The National Institute of Occupational Safety and Health (NIOSH), has concluded that at higher temperatures roofing asphalt fumes are a potential occupational carcinogen. If this product is heated or comes in contact with heated material, avoid breathing fumes. This product may contain small amounts of polycyclic aromatic hydrocarbons (PAH's) which are recognized carcinogens in humans and experimental animals. Mouse skin painting studies of roofing asphalt vapor concentrate have shown evidence of tumor formation associated with localized skin irritation in recent studies. Inhalation studies of high airborne concentrations of asphalt/bitumen fumes in rats and mice produced bronchitis, pneumonitis, and lung changes such as fibrosis and cell damage.

## Section 12 - Ecological Information

**Ecological Fate**

- **Solvent naphtha (petroleum), light aromatic** - Fish: 9.22: 96 h Oncorhynchus myk mg/L LC50. Crustacea: 6.14: 48 h Daphnia magna mg/LEC50. **1,2,4-Trimethylbenzene** – Fish: 7.19 - 8.28: 96 h Pimephalespromelas mg/L LC50 flow-through. Crustacea: 6.14: 48 h Daphnia magna mg/LEC50

**Persistence/Degradability**

- No data available.

**Bioaccumulation Potential**

- No data available.

**Mobility in Soil**

- No data available

## Section 13 - Disposal Considerations

**Product**

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## Section 14 - Transportation Information

**DOT - United States - Department of Transportation** - Not Regulated when shipped in containers < 119 gallons (450 L)

**TDG - Canada Transportation of Dangerous Goods:** Tars, Liquids; UN1999; Hazard Class: 3; Packing Group: III

**TDG Transportation Other Information:** 1.33 -Not Restricted under General Exemption for small container packaging.

**IMO/IMDG –International Maritime Transport:** Tars, Liquids; UN1999; Hazard Class: 3; Packing Group: III

**IMO/IMDG Transportation Other Information-**IMDG Code 2.3.2.5 - exempted from marking, labeling & testing of packages.

**IATA - International Air Transportation Association** - TARS, LIQUID; UN1999; Hazard Class: 3; Packing Group: III.

## Section 15 - Regulatory Information

**SARA Hazard Classifications**

- Acute, Chronic

**Risk & Safety Phrases**

- California PROP 65: Asphalt and Asphalt Fumes may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.

Bituminous Fumes are PROP 65 listed. Asphalt is considered a bituminous material but would need to be heated in excess of 500°F to release fumes necessary for exposure. Normal use of this product does not require heating and the material is not recommended for heating by the manufacture.



**WARNING:** Cancer – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Other Flammability Rating

Per NFPA and DOT the product is classified as a combustible liquid.

| State Right To Know                         |            |     |     |     |
|---------------------------------------------|------------|-----|-----|-----|
| Component                                   | CAS        | MA  | NJ  | PA  |
| Mineral Spirits                             | 8052-41-3  | Yes | Yes | Yes |
| Asphalt                                     | 8052-42-4  | Yes | Yes | Yes |
| Aluminum                                    | 7429-90-5  | Yes | Yes | Yes |
| 1,2,4-Trimethylbenzene                      | 95-63-6    | Yes | Yes | Yes |
| Benzene, 1,3,5-trimethyl                    | 108-67-8   | Yes | No  | No  |
| Solvent naphtha (petroleum), light aromatic | 64742-95-6 | No  | No  | No  |

| Inventory                                   |             |           |      |
|---------------------------------------------|-------------|-----------|------|
| Component                                   | CAS         | EU EINECS | TSCA |
| Mineral Spirits                             | 8052-41-3   | Yes       | Yes  |
| Asphalt                                     | 8052-42-4   | Yes       | Yes  |
| Aluminum                                    | 7429-90-5   | Yes       | Yes  |
| 1,2,4-Trimethylbenzene                      | 95-63-6     | Yes       | Yes  |
| Benzene, 1,3,5-trimethyl                    | 108-67-8    | Yes       | Yes  |
| Solvent naphtha (petroleum), light aromatic | 64742-95-6  | Yes       | Yes  |
| Perlite                                     | 130885-09-5 | No Data   | Yes  |

### Canada - WHMIS - Classifications of Substances

|                                               |            |            |                                                                              |
|-----------------------------------------------|------------|------------|------------------------------------------------------------------------------|
| - Aluminum                                    | 7429-90-5  | 10% TO 20% | B6 (powder); Uncontrolled product according to WHMIS classification criteria |
| - 1,2,4-Trimethylbenzene                      | 95-63-6    | 1% TO 5%   | B3                                                                           |
| - Solvent naphtha (petroleum), light aromatic | 64742-95-6 | 1% TO 5%   | B3, D2B                                                                      |
| - Mineral Spirits                             | 8052-41-3  | 35% TO 45% | B3, D2B                                                                      |
| - Benzene, 1,3,5-trimethyl                    | 108-67-8   | 1% TO 5%   | B3                                                                           |

### U.S. - CERCLA/SARA - Section 313 - Emission Reporting

|                          |           |            |                                                    |
|--------------------------|-----------|------------|----------------------------------------------------|
| - Aluminum               | 7429-90-5 | 10% TO 20% | 1.0 % de minimis concentration (dust or fume only) |
| - 1,2,4-Trimethylbenzene | 95-63-6   | 1% TO 5%   | 1.0 % de minimis concentration                     |

## Section 16 - Other Information

|                                          |                                                                                                                                                                                        |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Last Revision Date</b>                | - 9-21-2020                                                                                                                                                                            |
| <b>Prepared By</b>                       | - GG Inc.                                                                                                                                                                              |
| <b>Disclaimer/Statement of Liability</b> | - This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information |

is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. The manufacturer does not accept liability for any loss or damage that may occur from the use of this information.